

## PRODUCT DATA SHEET

# Sikalastic®-3 Primer XP

(formerly Davco® Primer XP)

### ACRYLIC PRIMER

#### DESCRIPTION

Sikalastic®-3 Primer XP is a solvent based acrylic primer for concrete, masonry, dry wall or metal surface prior to laying liquid applied membrane.

#### USES

Primer for concrete, masonry, dry wall or metal surface.

#### CHARACTERISTICS / ADVANTAGES

To improve adhesion of Sika liquid applied membrane product on concrete, masonry, dry wall or metal surface.

#### PRODUCT INFORMATION

Packaging	20 litres / pail
Colour	Clear
Shelf Life	12 months from the date of production
Storage Conditions	Store properly in original, unopened and undamaged sealed packaging in dry conditions. Keep away from direct sunlight and frost.
Density	0.92 kg/l

#### APPLICATION INFORMATION

Consumption	Approximately 9 - 12 m <sup>2</sup> per litre depending on the substrate condition.
Drying Time	Drying time is approximately 15 - 30 minutes depending on temperature and substrate condition.

#### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

# APPLICATION INSTRUCTIONS

## SUBSTRATE PREPARATION

All dust, loose and friable material must be completely removed from all surfaces before application of the product and associated system products, preferably by industrial vacuuming equipment.

If existing coatings are not completely removed, there is a risk of wrinkling, peeling and detachment of the old coatings.

## APPLICATION

Apply directly from the pail. Ensure a clear sheen after application and allow to dry before applying Sika liquid applied membrane product.

For concrete and masonry substrates to be primed using Sikalastic®-3 Primer XP, the surfaces must be bare without any coating.

For priming on existing coating, carry out a small trial before full application to determine the compatibility of the materials.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: sales@sg.sika.com

www.sika.com.sg



### Product Data Sheet

Sikalastic®-3 Primer XP

May 2026, Version 01.02

020915951000000167

Sikalastic-3PrimerXP-en-SG-(05-2026)-1-2.pdf