



# ACRYLIC PRIMER

## WATER BASED ACRYLIC PRIMER

### DESCRIPTION

Davco Acrylic Primer is a water based, acrylic primer to prepare surfaces prior to the application of liquid applied waterproofing membranes and wall coating systems.

### USES

- Primer and bonding agent on smooth concrete finishes
- Primer for absorbent surfaces for water-based Sikalastic® / Davco roofing systems
- Dust reducer and to increase abrasion resistance of the substrate
- Pore sealer on rough porous concrete to eliminate air bubbles

### SURFACE PREPARATION

Ensure that surface are dry and clean and free from curing compound or release agents.

No chipping or roughening of surface is required if the condition is stable. Old paint work which are stable can remain.

Any contamination including commercial detergents used for cleaning must be thoroughly rinsed off with plenty of water.

### TECHNICAL DATA

#### Physical Properties

Specific Gravity	1.01
Flash Point	Non Flammable
Drying Time	30 min
Water Resistance	Very Good

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### Sika (Singapore) Pte Ltd.

28 Tuas South Avenue 8 Singapore 637648  
Tel: (65) 6861 0632 • Fax: (65) 6862 1172  
Email: sales@sg.sika.com  
Website: www.sika.com.sg  
Online Store: davco-online.com.sg

### APPLICATION

Apply Davco Acrylic Primer to clean floor with roller, brush and squeegee. Allow to dry till clear film appears. Primer is dry when all milkiness disappears.

### COVERAGE

5 - 10m<sup>2</sup> per litre depending on the substrate condition.

### PACKAGING

Davco Acrylic Primer is available in 20 Ltr containers

### SHELF LIFE

Shelf life of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the Primer.

### HEALTH AND SAFETY

In case of excessive skin contact, thoroughly flush with clean water. If ill effects occur, seek medical attention promptly. Refer to safety data sheet.

#### Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website [www.sika.com.sg](http://www.sika.com.sg).