## **Davco GRS Primer**



Version	Revision Date:	SDS Number:	Date of last issue: 21.09.2020
2.0	26.06.2022	10000034130	Date of first issue: 21.09.2020

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name	Davco GRS Primer
Product code	: 10000034130
Manufacturer or supplier's	details
Company	: Sika (Singapore) Pte Ltd.
Telephone Telefax E-mail address Emergency telephone num- ber	28 Tuas South Ave 8 637648 Singapore : +65 6861 0632 : +65 6862 3915 : - : +65 6861 0632

### 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	:	Category 3
Acute toxicity (Inhalation)	:	Category 4
Acute toxicity (Dermal)	:	Category 4
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 2
Respiratory sensitisation	:	Category 1
Skin sensitisation	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2
Aspiration hazard	:	Category 1
GHS label elements Hazard pictograms	:	

# **Davco GRS Primer**



Version 2.0	Revision Date: 26.06.2022	SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
Signa	l word	: Danger	
Hazaı	rd statements	H315 Causes skin irritatior H317 May cause an allerg H319 Causes serious eye H334 May cause allergy o difficulties if inhaled. H335 May cause respirato	owed and enters airways. ontact with skin or if inhaled. n. ic skin reaction. irritation. r asthma symptoms or breathing ory irritation. to organs through prolonged or re-
Preca	utionary statements	No smoking. P233 Keep container tight P240 Ground/bond contair P241 Use explosion-proof ment. P242 Use only non-sparkin P243 Take precautionary of P260 Do not breathe mist P264 Wash skin thorough P271 Use only outdoors of P272 Contaminated work of the workplace.	ner and receiving equipment. electrical/ ventilating/ lighting equip- ng tools. measures against static discharge. or vapours. ly after handling. r in a well-ventilated area. clothing should not be allowed out of ves/ eye protection/ face protection.
		CENTER/ doctor. P303 + P361 + P353 IF OI ly all contaminated clothing P304 + P340 + P312 IF IN and keep comfortable for k doctor if you feel unwell. P305 + P351 + P338 IF IN for several minutes. Remo easy to do. Continue rinsir P331 Do NOT induce vom P333 + P313 If skin irritation vice/ attention. P337 + P313 If eye irritation tention. P342 + P311 If experiencing POISON CENTER/ doctor P362 + P364 Take off con reuse.	niting. on or rash occurs: Get medical ad- on persists: Get medical advice/ at- ng respiratory symptoms: Call a



Version 2.0	Revision Date: 26.06.2022	SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
		alcohol-resistant foam to e	xtinguish.
		tightly closed.	ell-ventilated place. Keep container
		Disposal:	
		P501 Dispose of contents/ disposal plant.	container to an approved waste
Other	hazards which do not	result in classification	

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

: Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 70 -< 90
ethylbenzene	100-41-4	>= 20 -< 30
4,4'-Methylenediphenyl diisocyanate, oligomer- ic reaction products with .alphahydro.omega hydroxypoly[oxy(methyl-1,2-ethanediyl)] and polyethoxylated and polypropoxylated glycerol	64298-75-5	>= 1 -< 10
Asphalt	8052-42-4	>= 1 -< 10

#### 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
		3/12

## **Davco GRS Primer**



Versio 2.0	VersionRevision Date:2.026.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020	
			Take victim immediately to hos	spital.	
	Most important symptoms and effects, both acute and delayed	:	<ul> <li>Risk of serious damage to the lungs (by aspiration). irritant effects sensitising effects</li> <li>Aspiration may cause pulmonary oedema and pneumonitis.</li> <li>Asthmatic appearance</li> <li>Cough</li> <li>Respiratory disorder</li> <li>Allergic reactions</li> <li>Excessive lachrymation</li> <li>Headache</li> <li>Dermatitis</li> <li>Skin disorders</li> <li>See Section 11 for more detailed information on health effects and symptoms.</li> <li>May be fatal if swallowed and enters airways.</li> <li>Harmful in contact with skin or if inhaled.</li> <li>Causes skin irritation.</li> <li>May cause an allergic skin reaction.</li> <li>Causes serious eye irritation.</li> <li>May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.</li> <li>May cause respiratory irritation.</li> <li>May cause damage to organs through prolonged or repeated exposure if inhaled.</li> </ul>		
	Notes to physician	:	Treat symptomatically.		
5. FI	REFIGHTING MEASURES				
	Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical		
	Unsuitable extinguishing media	:	Water		
	Hazardous combustion prod- ucts	:	No hazardous combustion pro-	ducts are known	
	Specific extinguishing meth- ods	:	Use water spray to cool unope	ned containers.	
	Special protective equipment for firefighters	:	In the event of fire, wear self-c	ontained breathing apparatus.	

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :	Use personal protective equipment.
tive equipment and emer-	Remove all sources of ignition.

## **Davco GRS Primer**



Version 2.0	Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
genc	y procedures		Deny access to unprotected pe	ersons.
Envir	onmental precautions	:	Prevent product from entering If the product contaminates rive respective authorities.	
	ods and materials for ainment and cleaning up	:	Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to loc / national regulations (see section 13).	
7. HANDI	ING AND STORAGE			
	ce on protection against nd explosion	:	Use explosion-proof equipmen Keep away from heat/ sparks/ smoking. Take precautionary measures es.	open flames/ hot surfaces. No
Advid	ce on safe handling	:	used. Smoking, eating and drinking s plication area. Take precautionary measures	on clothing. ction 8. sensitisation problems or asth- ent respiratory disease should as in which this mixture is being should be prohibited in the ap- against static discharge. e and/or exhaust in work rooms. at may be under pressure. d static electricity discharge organic vapours).
Conc	litions for safe storage	:	Store in original container. Keep in a well-ventilated place Containers which are opened r kept upright to prevent leakage Observe label precautions. Store in accordance with local	must be carefully resealed and e.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis



Version	Revision Date: 26.06.2022	SDS Number:	Date of last issue: 21.09.2020
2.0		100000034130	Date of first issue: 21.09.2020

		(Form of exposure)	ters / Permissible concentration	
xylene	1330-20-7	PEL (long term)	100 ppm 434 mg/m3	SG OEL
		PEL (short term)	150 ppm 651 mg/m3	SG OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	PEL (long term)	100 ppm 434 mg/m3	SG OEL
		PEL (short term)	125 ppm 543 mg/m3	SG OEL
		TWA	20 ppm	ACGIH
Asphalt	8052-42-4	PEL (long term) (Fumes)	5 mg/m3	SG OEL
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH

#### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	methylhip- puric acid	Urine		1.5 g/g creat- inine	SG BTLV
		Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure ceases)	1.5 g/g creat- inine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after ex- posure ceases)	0.15 g/g cre- atinine	ACGIH BEI

### Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling



Version 2.0	Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020	
			chemical products if a risk assessesses	sment indicates this is nec-	
Еуе рі	rotection	:	Safety eyewear complying with a be used when a risk assessment		
Skin and body protection		:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.		
Hygiei	ne measures	:	Handle in accordance with good practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and a		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	black
Odour	:	aromatic
Odour Threshold	:	No data available
рН	:	No data available
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	ca. 27.2 °C (81.0 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Vapour pressure	:	7.9993 hPa
Relative vapour density	:	No data available
Density	:	ca. 0.9 g/cm3 (25 °C (77 °F))
Solubility(ies)		

## **Davco GRS Primer**



Vers 2.0	on Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
	Water solubility		No data available	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n-	:	No data available	
	octanol/water Auto-ignition temperature	:	465 °C	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic	:	ca. 10 mPa.s	
	Viscosity, kinematic	:	No data available	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	

#### **10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.	
Chemical stability	:	The product is chemically stable.	
Possibility of hazardous reac- tions	:	Vapours may form explosive mixture with air. Stable under recommended storage conditions.	
Conditions to avoid	:	Heat, flames and sparks.	
Incompatible materials	:	No data available	

### **11. TOXICOLOGICAL INFORMATION**

Acute toxicity Harmful in contact with skin or if inhaled.

<u>Components:</u> xylene: Acute oral toxicity	:	LD50 Oral (Rat): 3,523 mg/kg
ethylbenzene: Acute oral toxicity	:	LD50 Oral (Rat): 3,500 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 5,510 mg/kg
		ate, oligomeric reaction products with .alphahydroomega nediyl)] and polyethoxylated and polypropoxylated glycerol

Acute oral toxicity : LD50 Oral (Rat): > 10,000 mg/kg

## **Davco GRS Primer**



ersion .0	Revision Date: 26.06.2022	SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
Acute	dermal toxicity	: LD50 Dermal (Rat): > 9,40	00 mg/kg
-	corrosion/irritation es skin irritation.		
	us eye damage/eye irrites serious eye irrites serious eye irritation.	ation	
Resp	iratory or skin sensitisa	ation	
	<b>sensitisation</b> cause an allergic skin rea	ction.	
	iratory sensitisation cause allergy or asthma s	symptoms or breathing difficult	ies if inhaled.
	<b>cell mutagenicity</b> assified based on availal	ble information.	
	<b>nogenicity</b> assified based on availal	ole information.	
-	oductive toxicity assified based on availal	ole information.	
	- single exposure cause respiratory irritatior	۱.	
	- repeated exposure cause damage to organs	through prolonged or repeated	d exposure if inhaled.
-	ation toxicity be fatal if swallowed and	enters airways.	
12. ECOL	OGICAL INFORMATION	l	
Ecoto	oxicity		
	oonents:		
xylen	e: ity to algae/aquatic	: EC50 (Pseudokirchneriell mg/l Exposure time: 72 h Method: OECD Test Guid	a subcapitata (green algae)): 2.2 leline 201

Toxicity to fish (Chronic tox-<br/>icity):NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l<br/>Exposure time: 56 d

Toxicity to daphnia and other	:	NOEC (Daphnia (water flea)): 1.17 mg/l
aquatic invertebrates (Chron-		Exposure time: 7 d
ic toxicity)		

### Persistence and degradability

No data available



Version 2.0	Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
	accumulative potential lata available			
	<b>ility in soil</b> lata available			
Othe	er adverse effects			
	<b>luct:</b> itional ecological infor- on	:	Harmful to aquatic life with lo	ng lasting effects.
13. DISP	OSAL CONSIDERATION	IS		
Disp	oosal methods			
•	te from residues		The product should not be all courses or the soil. Do not contaminate ponds, w cal or used container. Send to a licensed waste ma	vaterways or ditches with chemi-
Cont	taminated packaging		Empty remaining contents. Dispose of as unused produc Do not re-use empty containe Do not burn, or use a cutting	ers.

### 14. TRANSPORT INFORMATION

### International Regulations

ι	J١		R	I	D	G	
	IN	τ.				١.,	

UN number	:	UN 1263
Proper shipping name		PAINT RELATED MATERIAL
		(Xylene, Cutback Asphalt 60/70 90% in Xylene)
Class	:	3
Packing group	:	III
Labels	:	3
IATA-DGR		
UN/ID No.		UN 1263
	•	
Proper shipping name	:	Paint related material
		(Xylene, Cutback Asphalt 60/70 90% in Xylene)
Class	:	3
Packing group	:	
Labels	:	Flammable Liquids
Packing instruction (cargo	:	366
aircraft)		
Packing instruction (passen-	:	355
ger aircraft)		

#### IMDG-Code



Version 2.0	Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020		
2.0	20.00.2022		10000001100	Date of mot 10000. 21.00.2020		
UN nu	UN number		UN 1263			
Proper shipping name		:	PAINT RELATED MATERIAL (Xylene, Cutback Asphalt 60/70 90% in Xylene)			
Class		:	3	- /		
Packing group Labels		:	111			
		:	3			
EmS	Code	:	F-E, <u>S-E</u>			
Marin	e pollutant	:	no			

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations : Not applicable

#### **16. OTHER INFORMATION**

Date format	:	dd.mm.yyyy					
Full text of other abbreviations							
ACGIH ACGIH BEI SG BTLV SG OEL	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Singapore. Biological Threshold Limit Values Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.					
ACGIH / TWA ACGIH / STEL SG OEL / PEL (long term) SG OEL / PEL (short term) ADR	:	8-hour, time-weighted average Short-term exposure limit Permissible Exposure Level (PEL) Long Term Permissible Exposure Level (PEL) Short Term European Agreement concerning the International Carriage of Dangerous Goods by Road					
CAS DNEL EC50 GHS IATA	:	Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association					



Version 2.0	Revision Date: 26.06.2022		SDS Number: 100000034130	Date of last issue: 21.09.2020 Date of first issue: 21.09.2020
IMDG LD50		:	International Maritime Code for Da Median lethal dosis (the amount of once, which causes the death of 5	of a material, given all at
LC50		:	test animals) Median lethal concentration (conc air that kills 50% of the test anima period)	
MARPOL			International Convention for the P Ships, 1973 as modified by the Pr	
OEL		:	Occupational Exposure Limit	
PBT		:	Persistent, bioaccumulative and to	oxic
PNEC		:	Predicted no effect concentration	
REACH		:	Regulation (EC) No 1907/2006 of and of the Council of 18 December istration, Evaluation, Authorisation cals (REACH), establishing a Euro	er 2006 concerning the Reg- and Restriction of Chemi-
SVHC		:	Substances of Very High Concern	
vPvB		:	Very persistent and very bioaccur	nulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN