

## PRODUCT DATA SHEET

# Sikafloor®-2046 Neutral Filler

(formerly Davco® Neutral Filler)

### ACRYLIC COPOLYMER WITH FINE AGGREGATES

#### DESCRIPTION

Sikafloor®-2046 Neutral Filler is a good weather-resistant acrylic copolymer with fine aggregates for excellent anti-skid resistance. It is used together with Sikafloor®-2045 Courtkote as part of the sports surfacing system.

#### USES

Sikafloor®-2046 Neutral Filler may only be used by experienced professionals.

- Hardcourt surfaces for sports, e.g. basketball, tennis courts
- Cycling paths
- Playgrounds
- Other hard surface areas

#### CHARACTERISTICS / ADVANTAGES

- Ease of application as it is ready to use.
- Good anti-skid resistance.
- Tough and durable surface.
- Suitable for use in exterior application.

#### PRODUCT INFORMATION

<b>Packaging</b>	22 ltr/pail	
<b>Shelf Life</b>	12 months from the date of production	
<b>Storage Conditions</b>	Store properly in original, unopened and undamaged containers in dry conditions. Keep away from direct sunlight and frost.	
<b>Density</b>	1.45 ± 0.05 kg/m <sup>3</sup>	(ASTM D4052)

#### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

#### APPLICATION INSTRUCTIONS

##### SUBSTRATE PREPARATION

The surface to be painted must be dry and clean, free of loose particles, dust, grease, oil, wax, grease, algae/fungus etc.

Any old and loose coatings should be removed and surface thoroughly cleaned before application.

##### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's cur-

rent knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: sales@sg.sika.com

www.sika.com.sg



**Product Data Sheet**

**Sikafloor®-2046 Neutral Filler**

March 2025, Version 01.03

020813020010000070

