

## PRODUCT DATA SHEET

# SikaProof® Fix Tape-50

DOUBLE-SIDED SELF-ADHESIVE TAPE FOR DETAILING SIKAPROOF A WATERPROOFING SYSTEM

### DESCRIPTION

SikaProof® Fix Tape-50 is a double-sided, self-adhesive tape, consisting of a butyl rubber adhesive that is covered with a release liner.

### USES

SikaProof® Fix Tape-50 may only be used by experienced professionals.

- Waterproofing various detailing configurations within the SikaProof® A Waterproofing System.

### CHARACTERISTICS / ADVANTAGES

- Good adhesion of the butyl rubber adhesive
- Good durability
- Self adhesion allows easy and fast installation

### PRODUCT INFORMATION

<b>Packaging</b>	5 rolls packed in one box
<b>Appearance / Colour</b>	White release liner over black butyl rubber adhesive.
<b>Shelf Life</b>	24 months from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.
<b>Length</b>	20 m
<b>Width</b>	50 mm
<b>Thickness</b>	1.50 mm

### SYSTEM INFORMATION

<b>System Structure</b>	SikaProof® Fix Tape-50 must be used with the following: <ul style="list-style-type: none"> <li>▪ SikaProof® A sheet membrane waterproofing system</li> </ul>
-------------------------	--

### APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	+5 °C min. / +35 °C max.
<b>Substrate Temperature</b>	+5 °C min. / +35 °C max.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surfaces of the membrane must be dry, clean and free of materials that could impair adhesion.

### APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Reference must be made to the Sika® Method Statement: SikaProof® A membrane

### FURTHER DOCUMENTS

- Sika® Method Statement: SikaProof® A membrane
- System Data Sheet: SikaProof® A membrane

### LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- SikaProof® Fix Tape-50 is not UV stabilised and must not be installed on structures that permanently exposes the membrane to UV light and weathering.
- Do not apply the SikaProof® Fix Tape-50 during continuous or prolonged rainfall.

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.

### REGULATION (EC) NO 1907/2006 - REACH

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

#### Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: sales@sg.sika.com

www.sika.com.sg



#### Product Data Sheet

SikaProof® Fix Tape-50

May 2020, Version 02.01

020720308000000004

SikaProofFixTape-50-en-SG-(05-2020)-2-1.pdf