

PRODUCT DATA SHEET

SikaProof®-936 UVS

(formerly MSeal 936UVS)

DOUBLE-SIDED STICKY TAPE FOR SikaProof®-730 PA HDPE PRE-APPLIED WATERPROOFING SYSTEM

DESCRIPTION

SikaProof®-936 UVS is a white or light yellow double sided sticky, HDPE self-adhesive tape. It is designed for use in underground waterproofing termination detailing along with SikaProof®-730 PA membrane system.

USES

SikaProof®-936 UVS is used for end lap treatment as part of the SikaProof®-730 PA membrane system. SikaProof®-936 UVS is applied to waterproofing and damp-proofing engineering's for various underground building structures and basements.

CHARACTERISTICS / ADVANTAGES

The specially-made high density thermoplastic polyethylene (HDPE) film works as a waterproof base material. On both sides the HDPE film is covered with macromolecule self-adhesive film and on the exposed surface the composite adhesive. The weather-resistant protective and insulating layer, belongs to macromolecule selfadhesive film.

PRODUCT INFORMATION

Packaging	80 mm x 50 m x 0.3 mm thickness double side sticky tape.
Shelf Life	12 months from date of production
Storage Conditions	stored in unopened, undamaged, original packaging in dry conditions and at temperatures between +5°C and +30°C.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION

SikaProof®-936 UVS is part of the SikaProof®-730 PA system, please refer to the relevant method statement or contact your local Sika Technical Services department.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8
Singapore 637648
Phone: +65 6861 0632
Fax: +65 6862 3915
Email: sales@sg.sika.com
www.sika.com.sg



Product Data Sheet

SikaProof®-936 UVS
September 2024, Version 02.01
02072000000002009