



Davco

SUPAPRIME

PENETRATING PRIMER

DESCRIPTION

Davco Supaprime is a single component solvent based system which is formulated using acrylic resin combined with special additives for enhanced adhesion.

USES

As a primer on concrete, plywood and solvent based membrane to provide substrate with excellent adhesion to cement based products.

SURFACE PREPARATION

For new or old substrates, surfaces should be free from dirt, grease, fungus/algae and any loose matter.

Surface should be dry and free from stains.

New concrete surface should have a minimum of 7 days curing period.

TECHNICAL DATA

Density	: 1410 kg/L
Touch dry	: 1 - 2 hours @ 23 °C
Fully cured	: 1 - 2 days
Flash point	: 40 °C
Solid by weight	: 60%

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

APPLYING THE MATERIAL

No mixing is required, just stir the material before use to prevent settlement due to storage and transportation.

Apply Davco Supaprime directly from the can.

Apply 1 - 2 coats using brush or roller.

Ensure the surface is dry before applying Davco Supaprime.

Sika (Singapore) Pte Ltd.

28 Tuas South Avenue 8 Singapore 637648

Tel: (65) 6861 0632 • Fax: (65) 6862 1172

Email: sales@sg.sika.com

Website: www.sika.com.sg

Online Store: davco-online.com.sg

COVERAGE

Depending on the porosity of the surface to be applied, 2.5m²/L @ 150 μ thick. (As a guide for concrete surface)

PACKAGING

Available in 20 litres pail.

SHELF LIFE

Shelf life of 6 months when stored in a cool dry place in unopened containers.

CLEANING

Tools and equipment must be cleaned immediately after use with aromatic solvent.

HEALTH AND SAFETY

This product contains solvent and is flammable. Do not use near naked flame or smoke during handling. Wear protective gloves and safety goggles. Avoid excessive inhalation. In case of skin contact or accidental eye contamination, wash with plenty of clean water. Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.sika.com.sg



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



Certificate GMS-C / GHG / 0002

