Davco Tufseal



Version 2.0	Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021
1. PRODU	CT AND COMPANY IDEN	NTIFI	CATION	
Produ	ct name	: D	avco Tufseal	

Manufacturer or supplier's details										
Company	:	Sika (Singapore) Pte Ltd.								
		28 Tuas South Ave 8 637648 Singapore								
Telephone	:	+65 6861 0632								
Emergency telephone number	:	+65 6861 0632								
E-mail address	:	-								
Telefax	:	+65 6862 3915								

2. HAZARDS IDENTIFICATION

	GHS Classification		
	Flammable liquids	:	Category 3
	Acute toxicity (Inhalation)	:	Category 4
I	Acute toxicity (Dermal)	:	Category 4
	Skin corrosion/irritation	:	Category 2
	Serious eye damage/eye irri- tation	:	Category 2
	Reproductive toxicity	:	Category 2
	Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system)
	Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2
	Aspiration hazard	:	Category 1

GHS label elements

Davco Tufseal



Version 2.0	Revision Date: 27.12.2022	SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021
Hazaro	d pictograms		
Signal	word	: Danger	\checkmark
Hazaro	d statements	H315 Causes skin irritation H319 Causes serious eye H335 May cause respirato H361 Suspected of damag	owed and enters airways. contact with skin or if inhaled. n. irritation. ory irritation. ging fertility or the unborn child. to organs through prolonged or re-
Precau	utionary statements	and understood. P210 Keep away from hea No smoking. P233 Keep container tight P240 Ground/bond contain P241 Use explosion-proof ment. P242 Use only non-sparkin P243 Take precautionary i P260 Do not breathe mist P264 Wash skin thorough P271 Use only outdoors o	all safety precautions have been read at/ sparks/ open flames/ hot surfaces. ly closed. ner and receiving equipment. electrical/ ventilating/ lighting equip- ng tools. measures against static discharge. or vapours. ly after handling.
		CENTER/ doctor. P303 + P361 + P353 IF O ly all contaminated clothing P304 + P340 + P312 IF IN and keep comfortable for b doctor if you feel unwell. P305 + P351 + P338 IF IN for several minutes. Remo easy to do. Continue rinsir P308 + P313 IF exposed of attention. P331 Do NOT induce vom P332 + P313 If skin irritation tion.	or concerned: Get medical advice/



Version 2.0	Revision Date: 27.12.2022	SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021			
		reuse.	aminated clothing and wash it before e: Use dry sand, dry chemical or xtinguish.			
		Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.				
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste			
Other	hazards which do not	result in classification				

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
---------------------	---	---------

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 50 -< 70
ethylbenzene	100-41-4	>= 10 -< 20
toluene	108-88-3	>= 3 -< 10

4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.
		3/12

Davco Tufseal



Vers 2.0	ion Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021
	Most important symptoms and effects, both acute and delayed	:	 Risk of serious damage to the lungs (by aspiration). irritant effects Aspiration may cause pulmonary oedema and pneumonitis. Cough Respiratory disorder Excessive lachrymation Headache Dermatitis Skin disorders See Section 11 for more detailed information on health effects and symptoms. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if inhaled. 	
	Notes to physician	:	Treat symptomatically.	
5. F	IREFIGHTING MEASURES			
	Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
	Unsuitable extinguishing media	:	Water High volume water jet	
	Specific hazards during fire- fighting	:	Do not use a solid water stream a fire.	s it may scatter and spread
	Hazardous combustion prod- ucts	:	No hazardous combustion produc	ts are known
	Specific extinguishing meth- ods	:	Use water spray to cool unopened	d containers.
	Special protective equipment for firefighters	:	In the event of fire, wear self-cont	ained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.
Environmental precautions	:	Prevent product from entering drains.

Davco Tufseal



Version 2.0	Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021	
			If the product contaminates respective authorities.	rivers and lakes or drains inform	
	Methods and materials for : containment and cleaning up		Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).		
7. HANDL	ING AND STORAGE				
	e on protection against nd explosion	:	smoking.	ent. s/ open flames/ hot surfaces. No es against electrostatic discharg-	
Advic	Advice on safe handling		Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products		
Cond	Conditions for safe storage :		Store in original container. Keep in a well-ventilated pla Containers which are opene kept upright to prevent leaka Observe label precautions. Store in accordance with loc	d must be carefully resealed and age.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
xylene	1330-20-7	PEL (long	100 ppm	SG OEL
		term)	434 mg/m3	
		PEL (short	150 ppm	SG OEL
		term)	651 mg/m3	
		TWA	20 ppm	ACGIH
ethylbenzene	100-41-4	PEL (long	100 ppm	SG OEL

Components with workplace control parameters



Version 2.0	Revision Date: SDS Number: 27.12.2022 100000033907			Date of last issue: 15.09.2021 Date of first issue: 15.09.2021			
			term)	434 mg/m3	1 1		
			PEL (short term)	125 ppm 543 mg/m3	SG OEL		
			TWA	20 ppm	ACGIH		
toluen	e	108-88-3	PEL (long term)	50 ppm 188 mg/m3	SG OEL		
			TWA	20 ppm	ACGIH		

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
xylene	1330-20-7	methylhip- puric acid	Urine		1.5 g/g creat- inine	SG BTLV
		Methylhip- puric acids	Urine	End of shift (As soon as possible after ex- posure ceases)	1.5 g/g creat- inine	ACGIH BEI
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after ex- posure ceases)	0.15 g/g cre- atinine	ACGIH BEI
toluene	108-88-3	toluene	Blood	Prior to last shift of work- week	0.05 mg/l	SG BTLV
		Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after ex- posure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after ex- posure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust

Davco Tufseal



Version 2.0	Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021	
			that exposures are within re The filter class for the respir imum expected contaminan (gas/vapour/aerosol/particul	lates) that may arise when han- centration is exceeded, self-	
Hand protection		:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.		
Eye protection		:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.		
Skin a	Skin and body protection		Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.		
Hygie	ne measures	:	Handle in accordance with g practice. When using do not eat or dr When using do not smoke. Wash hands before breaks		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless
Odour	:	aromatic
Odour Threshold	:	No data available
рН	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 27.2 °C (81.0 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	7 %(V)

Davco Tufseal



Vers 2.0	sion	Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021
	Lower ex flammab	•	:	1 %(V)	
	Vapour pressure		:	7.9993 hPa	
	Relative vapour density		:	No data available	
	Density		:	ca. 0.91 g/cm3 (25 °C (77 °F))	
	Solubility Water	r(ies) r solubility	:	insoluble	
	Solub	ility in other solvents	:	No data available	
		coefficient: n-	:	No data available	
	octanol/v Auto-igni	tion temperature	:	465 °C	
	Decompo	osition temperature	:	No data available	
	Viscosity Visco	sity, dynamic	:	ca. 30 mPa.s	
	Visco	sity, kinematic	:	No data available	
	Explosive	e properties	:	No data available	
	Oxidizing	properties	:	No data available	

10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Vapours may form explosive mixture with air. Stable under recommended storage conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful in contact with skin or if inhaled.

Components:

xylene: Acute oral toxicity

: LD50 Oral (Rat): 3,523 mg/kg

Davco Tufseal



Version 2.0	Revision Date: 27.12.2022	SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021					
	benzene: e oral toxicity	: LD50 Oral (Rat): 3,500) mg/kg					
Acute	e dermal toxicity	: LD50 Dermal (Rabbit):	5,510 mg/kg					
	corrosion/irritation es skin irritation.							
	ous eye damage/eye ir es serious eye irritatior							
Resp	iratory or skin sensit	isation						
• • • • • • • • • • • • • • • • • • • •	sensitisation lassified based on avai	lable information.						
•	Respiratory sensitisation Not classified based on available information.							
	Germ cell mutagenicity Not classified based on available information.							
	i nogenicity lassified based on avai	lable information.						
-	oductive toxicity ected of damaging ferti	lity or the unborn child.						
	F - single exposure cause respiratory irritat	ion.						
	F - repeated exposure cause damage to orgar	ns through prolonged or repea	ated exposure if inhaled.					
-	r ation toxicity be fatal if swallowed an	d enters airways.						
12. ECOL	OGICAL INFORMATIC	ON						
Ecoto	oxicity							
	ponents:							
xylen Toxic icity)	ie: ity to fish (Chronic tox-	: NOEC (Oncorhynchus Exposure time: 56 d	mykiss (rainbow trout)): > 1.3 mg/l					

Toxicity to daphnia and other	:	NOEC (Daphnia (water flea)): 1.17 mg/l
aquatic invertebrates (Chron-		Exposure time: 7 d
ic toxicity)		

Persistence and degradability

No data available



Versic 2.0	on Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021
	Bioaccumulative potential No data available			
	Mobility in soil No data available			
(Other adverse effects			
,	Product: Additional ecological infor- mation	:	Harmful to aquatic life with long la	asting effects.
13. D	ISPOSAL CONSIDERATION	IS		
I	Disposal methods			
\	Waste from residues	:	Send to a licensed waste manage	ement company.
			The product should not be allowe courses or the soil. Do not contaminate ponds, water cal or used container.	
(Contaminated packaging	:	Empty remaining contents. Dispose of as unused product.	
			Do not re-use empty containers. Do not burn, or use a cutting torcl	n on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG		
UN number or ID number	:	UN 1307
Proper shipping name	:	XYLENES
		(Xylene)
Class	:	3
Packing group	:	III
Labels	:	3
IATA-DGR		
UN/ID No.	•	UN 1307
Proper shipping name		Xylenes
rieper empping name	•	(Xylene)
Class	:	3
Packing group	:	111
Labels	:	Flammable Liquids
Packing instruction (cargo	:	366
aircraft)		
Packing instruction (passen-	:	355
ger aircraft)		

Davco Tufseal



VersionRevision Date:SDS Number:Date of last issue: 15.09.20212.027.12.2022100000033907Date of first issue: 15.09.2021
--

IMDG-Code		
UN number or ID number	:	UN 1307
Proper shipping name	:	XYLENES
		(Xylene)
Class	:	3
Packing group	:	111
Labels	:	3
EmS Code	:	F-E, S-D
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations : Not applicable

16. OTHER INFORMATION

Revision Date Date format	:	27.12.2022 dd.mm.yyyy			
Full text of other abbreviations					
ACGIH ACGIH BEI SG BTLV	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Singapore. Biological Threshold Limit Values			
SG OEL	:	Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.			
ACGIH / TWA	:	8-hour, time-weighted average			
SG OEL / PEL (long term)	:				
SG OEL / PEL (short term)	:				
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road			
CAS	:	Chemical Abstracts Service			
DNEL	:	Derived no-effect level			
EC50	:	Half maximal effective concentration			
GHS	:	Globally Harmonized System			



Version 2.0	Revision Date: 27.12.2022		SDS Number: 100000033907	Date of last issue: 15.09.2021 Date of first issue: 15.09.2021		
IATA			International Air Transport As	ssociation		
IMDG		÷	: International Maritime Code for Dangerous Goods			
LD50		:	Median lethal dosis (the amo			
LC50		:		concentrations of the chemical in nimals during the observation		
MARPO	L	:	International Convention for t Ships, 1973 as modified by th	the Prevention of Pollution from the Protocol of 1978		
OEL		:	Occupational Exposure Limit			
PBT		:	Persistent, bioaccumulative a			
PNEC		:	Predicted no effect concentra	ation		
REACH		:	and of the Council of 18 Dec istration, Evaluation, Authoris	D6 of the European Parliament ember 2006 concerning the Reg- sation and Restriction of Chemi- a European Chemicals Agency		
SVHC		:	Substances of Very High Cor			
vPvB		:	Very persistent and very bioa	accumulative		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN