

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikadur® -31 CF Normal Part A

Product code : 100000006826

Manufacturer or supplier's details

Company : **Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8
637648 Singapore

Telephone : +65 6861 0632

Telefax : +65 6862 3915

E-mail address : -

Emergency telephone number : +65 6861 0632

Recommended use of the chemical and restrictions on use

Product use : Adhesive

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	25068-38-6	\geq 20 -< 25
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	\geq 1 -< 10
(1-methylethyl)-1,1'-biphenyl	25640-78-2	\geq 1 -< 2.5

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
-

9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version	Revision Date:	SDS Number:	Date of last issue: 13.04.2019
2.0	12.04.2022	100000006826	Date of first issue: 13.04.2019

Appearance	:	paste
Colour	:	grey
Odour	:	epoxy-like
Odour Threshold	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C (214 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.01 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.94 g/cm ³ (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	Not applicable
	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (40 °C (104 °F))
Explosive properties	:	No data available

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

(1-methylethyl)-1,1'-biphenyl:

Acute oral toxicity : LD50 Oral (Rat): 4,650 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 0.167 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemi-

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

cal or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo : 956
aircraft)
Packing instruction (passen- : 956
ger aircraft)

IATA-DGR

Transport in accordance with special regulation A 197

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

IMDG-Code

Transport in accordance with 2.10.2.7 of the IMDG-Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable
Environmental Protection and Management (Hazardous Substances) Regulations

16. OTHER INFORMATION

Date format : dd.mm.yyyy

Full text of other abbreviations

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET

Sikadur® -31 CF Normal Part A



Version
2.0

Revision Date:
12.04.2022

SDS Number:
100000006826

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

SG / EN