Sikalastic[®]-632 R



Version	Revision Date:	SDS Number:	Date of last issue: -
2.0	14.07.2022	10000017461	Date of first issue: 20.03.2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name	Sikalastic [®] -632 R
Product code	: 100000017461
Manufacturer or supplier's of	details
Company	: Sika (Singapore) Pte Ltd.
Telephone Telefax E-mail address Emergency telephone num- ber	28 Tuas South Ave 8 637648 Singapore : +65 6861 0632 : +65 6862 3915 : - : +65 6861 0632

2. HAZARDS IDENTIFICATION

GHS Classification		
Flammable liquids	:	Category 3
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irri- tation	:	Category 1
Skin sensitisation	:	Category 1
GHS label elements		
Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage.
Precautionary statements	:	Prevention:
		 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

Sikalastic[®]-632 R



Version 2.0	Revision Date: 14.07.2022	SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019			
		P261 Avoid breathing mist P264 Wash skin thoroughl P272 Contaminated work of the workplace.	measures against static discharge.			
		Response:				
		 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediated ly all contaminated clothing. Rinse skin with water/ shower. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it befor reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. 				
		Storage:				
		P403 + P235 Store in a well-ventilated place. Keep cool.				
		Disposal:				
		P501 Dispose of contents/ disposal plant.	container to an approved waste			
II Other	hazards which do not	result in classification				

Other hazards which do not result in classification None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
polyurethane prepolymere	Not Assigned	>= 30 -< 50
Isophorondiamine-Isobutyraldimine	54914-37-3	>= 3 -< 5
Hydrocarbons, C9, aromatics	64742-95-6	>= 2.5 -< 10
2-methoxy-1-methylethyl acetate	108-65-6	>= 1 -< 10
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 0.1 -< 0.25
bis(2-ethylhexyl) phthalate	117-81-7	>= 0.1 -< 0.3

4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.
	2 / 10

Sikalastic[®]-632 R



Version 2.0	Revision Date: 14.07.2022		SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019	
			Consult a physician after sigr	nificant exposure.	
In cas	In case of skin contact		Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
In cas	In case of eye contact		Small amounts splashed into eyes can cause irreversible tis- sue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.		
lf swa	If swallowed		Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.		
and e	Most important symptoms and effects, both acute and delayed		irritant effects sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more deta and symptoms. Causes skin irritation. May cause an allergic skin re Causes serious eye damage.		
Notes	to physician	:	Treat symptomatically.		
5. FIREFIC	GHTING MEASURES				
Suital	ble extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical		
Unsu media	itable extinguishing	:	Water		
Haza ucts	rdous combustion prod-	: No hazardous combustion products are known		oducts are known	
Speci	Specific extinguishing meth- : Use water spray to cool unopened containers.		pened containers.		

6. ACCIDENTAL RELEASE MEASURES

ods

Sikalastic[®]-632 R



Versio 2.0	on Revision Date: 14.07.2022		SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019
	Personal precautions, protec- tive equipment and emer- gency procedures		Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons.	
	Environmental precautions		Prevent product from entering dra If the product contaminates rivers respective authorities.	
	Methods and materials for containment and cleaning up		Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).	
7. HA	ANDLING AND STORAGE			
	Advice on protection against fire and explosion	:	Use explosion-proof equipment. Keep away from heat/ sparks/ ope smoking. Take precautionary measures aga es.	
	Advice on safe handling	:	Do not breathe vapours or spray in Avoid exceeding the given occupations section 8). Do not get in eyes, on skin, or on a For personal protection see section Persons with a history of skin sense ma, allergies, chronic or recurrent not be employed in any process in used. Smoking, eating and drinking show plication area. Take precautionary measures aga Open drum carefully as content m Take necessary action to avoid stat (which might cause ignition of orgat Follow standard hygiene measures products	ational exposure limits (see clothing. on 8. sitisation problems or asth- respiratory disease should on which this mixture is being uld be prohibited in the ap- ainst static discharge. ay be under pressure. atic electricity discharge anic vapours).
	Conditions for safe storage	:	Store in original container. Keep in a well-ventilated place. Containers which are opened must kept upright to prevent leakage. Observe label precautions. Store in accordance with local reg	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis

Sikalastic[®]-632 R



ersion Revision Date: 0 14.07.2022					Date of last issue: - Date of first issue: 20.03.2019	
				(Form of exposure)	ters / Permissible concentration	
bis(2-e	ethylhexyl) phthalate		117-81-7	PEL (long term)	5 mg/m3	SG OEL
				PEL (short term)	10 mg/m3	SG OEL
				TWÁ	5 mg/m3	ACGIH
Perso	nal protective equipr	nent				
Respi	ratory protection	:	ventilation is that exposure The filter clas imum expecte (gas/vapour/a dling the proc	provided or exp es are within rec s for the respira ed contaminant aerosol/particula duct. If this conc	nless adequate local e cosure assessment de commended exposure ator must be suitable f concentration ates) that may arise w centration is exceeded us must be used.	emonstrates guidelines. for the max- rhen han-
Hand	protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.			
Eye pi	rotection	:			ith an approved stand nent indicates this is i	
Skin a	nd body protection	:		nount of dange	elation to its type, to the rous substances, and	
Hygiei	ne measures	:	practice. When using o When using o	do not eat or dri do not smoke.	ood industrial hygiene nk. and at the end of work	·

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	various
Odour	:	mild
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available

Sikalastic[®]-632 R



Versi 2.0	on Revision Date: 14.07.2022		SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019
	Flash point		ca. 43 °C (109 °F) (Method: closed cup)	
	Evaporation rate	:	No data available	
	Flammability (solid, gas)	:	No data available	
	Upper explosion limit / Upper flammability limit		No data available	
	Lower explosion limit / Lower flammability limit	r :	No data available	
	Vapour pressure	:	0.01 hPa	
	Relative vapour density		No data available	
	Density		ca. 1.4 g/cm3 (20 °C (68 °F))	
	Solubility(ies) Water solubility	:	No data available	
	Solubility in other solvents	S :	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	333 °C	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic		ca. 4,300 mPa.s (25 °C (77 °F))	
	Viscosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	

10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available

Sikalastic[®]-632 R



ersion .0	Revision Date: 14.07.2022	SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019
1. TOXICO	OLOGICAL INFORMAT	ION	
	toxicity assified based on availa	ble information.	
Comp	onents:		
Isoph	orondiamine-Isobutyra	I dimine: : LD50 Oral (Rat): 4,150 mg	ı/kg
Acute	dermal toxicity	: LD50 Dermal (Rat): > 5,00	00 mg/kg
	carbons, C9, aromatic oral toxicity	s: : LD50 Oral (Rat): > 2,000 n	ng/kg
Acute	dermal toxicity	: LD50 Dermal (Rabbit): > 2	,000 mg/kg
	hoxy-1-methylethyl ac oral toxicity	e tate: : LD50 Oral (Rat): > 5,000 n	ng/kg
Acute	dermal toxicity	: LD50 Dermal (Rabbit): > 5	,000 mg/kg
	corrosion/irritation		
	us eye damage/eye irri es serious eye damage.	tation	
Respi	ratory or skin sensitis	ation	
	ensitisation ause an allergic skin rea	ction.	
-	ratory sensitisation assified based on availa	ble information.	
	cell mutagenicity assified based on availa	ble information.	
	nogenicity assified based on availa	ble information.	
-	ductive toxicity assified based on availa	ble information.	
	- single exposure assified based on availa	ble information.	
	- repeated exposure		
	assified based on availa ation toxicity	die information.	
-	assified based on availa	ble information.	

Sikalastic[®]-632 R



Revision Date: 14.07.2022	SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.201
OGICAL INFORMATION		
oxicity		
oonents:		
ocarbons, C9, aromatics: ty to algae/aquatic :	(Pseudokirchneriella subca mg/l Exposure time: 72 h	apitata (green algae)): 2.6 - 2.9
stence and degradability ta available		
cumulative potential ta available		
ity in soil ta available		
adverse effects		
ict: onal ecological infor- : n	An environmental hazard c unprofessional handling or Harmful to aquatic life with	
	14.07.2022 DGICAL INFORMATION xicity onents: carbons, C9, aromatics: ty to algae/aquatic : stence and degradability ta available cumulative potential ta available ity in soil ta available adverse effects ict: onal ecological infor- :	14.07.2022 100000017461 DGICAL INFORMATION xicity onents: poarbons, C9, aromatics: (Pseudokirchneriella subcomg/l mg/l Exposure time: 72 h stence and degradability ta available cumulative potential ta available adverse effects An environmental hazard of unprofessional handling or

Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	:	UN 1263
Proper shipping name	:	PAINT
Class	:	3

Sikalastic[®]-632 R



Versio 2.0	on Revision Date: 14.07.2022		SDS Number: 100000017461	Date of last issue: - Date of first issue: 20.03.2019
	Packing group Labels	:	 3	
	IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)		UN 1263 Paint 3 III Flammable Liquids 366 355	
	IMDG-Code UN number Proper shipping name Class Packing group Labels EmS Code Marine pollutant		UN 1263 PAINT 3 III 3 F-E, <u>S-E</u> no	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and Environmental Protection and Management (Hazardous Substances) Regulations : Not applicable

16. OTHER INFORMATION

	Date format	:	dd.mm.yyyy
Full text of other abbreviations			
	ACGIH SG OEL		USA. ACGIH Threshold Limit Values (TLV) Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.

Sikalastic[®]-632 R



Versior 2.0	n Revision Date: 14.07.2022		f last issue: - f first issue: 20.03.2019	
ACGIH / TWA SG OEL / PEL (long term) SG OEL / PEL (short term) ADR CAS DNEL EC50 GHS IATA IMDG LD50 LC50 MARPOL OEL		8-hour, time-weighted average Permissible Exposure Level (PEL) Long Term Permissible Exposure Level (PEL) Short Term European Agreement concerning the International Carriage of Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)		
		 Median lethal concentration (concentration air that kills 50% of the test animals during period) 		
		: International Convention for the Preventior Ships, 1973 as modified by the Protocol of		
	PBT	 Occupational Exposure Limit Persistent, bioaccumulative and toxic 		
	NEC	: Predicted no effect concentration		
R	REACH	: Regulation (EC) No 1907/2006 of the Euro and of the Council of 18 December 2006 of istration, Evaluation, Authorisation and Re cals (REACH), establishing a European Cl	oncerning the Reg- striction of Chemi-	
	SVHC PvB	Substances of Very High ConcernVery persistent and very bioaccumulative		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN