Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikagard®-61 TZ Part A

Manufacturer or supplier's details

Company : Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8 637648 Singapore

Telephone : +65 6861 0632

Emergency telephone number : +65 6861 0632

E-mail address : -

Telefax : +65 6862 3915

Recommended use of the chemical and restrictions on use

Product use : For professional users only., Epoxy coating

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2

Skin sensitisation : Category 1

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight	25068-38-6	>= 70 -< 90
≤ 700)	40000 04 4	4 40
1,6-bis(2,3-epoxypropoxy)hexane	16096-31-4	>= 1 -< 10
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 0.1 -< 1
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	>= 0.25 -< 1

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

100000006813 01.08.2022 Date of first issue: 01.08.2022 1.0

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

Clean mouth with water and drink afterwards plenty of water. If swallowed

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects

Allergic reactions **Excessive lachrymation**

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : various

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : $> 100 \, ^{\circ}\text{C} \, (> 212 \, ^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : < 1

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : > 17 mmHg

Relative vapour density : No data available

Density : ca. 1.45 g/cm3 (20 °C (68 °F))

Solubility(ies)

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

1,6-bis(2,3-epoxypropoxy)hexane:

Acute oral toxicity : LD50 Oral (Rat): 2,900 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

Sikagard®-61 TZ Part A



Date of last issue: -Version **Revision Date:** SDS Number:

100000006813 1.0 01.08.2022 Date of first issue: 01.08.2022

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h aquatic invertebrates

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

01.08.2022 100000006813 Date of first issue: 01.08.2022 1.0

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class 9 Ш Packing group Labels 9

IATA-DGR

UN/ID No.

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

Class 9 Ш Packing group

Miscellaneous Labels 964

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

ger aircraft)

IMDG-Code

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

9 Class Packing group Ш Labels 9 EmS Code F-A, S-F

Sikagard®-61 TZ Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 01.08.2022 100000006813 Date of first issue: 01.08.2022

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Not applicable

16. OTHER INFORMATION