

## PRODUCT DATA SHEET

# SikaRoof® VersiDrain® 60 Wall Joiner

## JOINER FOR WALL EXTENDER FOR EXTENSIVE GREEN ROOF PLANTING TRAY

### DESCRIPTION

SikaRoof® VersiDrain® 60 Wall Joiner is a joiner for wall extenders designed to allow wall extenders to be joined side to side, creating a single perimeter wall around the extensive green roof plot. Wall extenders are manufactured from recycled polypropylene (PP), and slot into two adjacent wall extenders to connect them.

SikaRoof® VersiDrain® 60 Wall Joiner is used in conjunction with SikaRoof® VersiDrain® 60 Wall Extender and SikaRoof® VersiDrain® 60 trays to increase the soil capacity of these trays enabling more diverse planting options.

### USES

Increased planting media capacity for extensive green roofs, landscape decks and lightweight green installations requiring water storage in combination with a suitable geotextile as a filtration layer to prevent planting media from clogging the reservoir and drainage layer.

### PRODUCT INFORMATION


|                            |  |
|----------------------------|--|
| <b>Packaging</b>           | ▪ SikaRoof® VersiDrain® 60 Wall Joiner<br>Refer to pricelist |
| <b>Appearance / Colour</b> | Black cuboid joiner  |

### CHARACTERISTICS / ADVANTAGES

- Increased planting media capacity
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

### APPROVALS / STANDARDS

Singapore Green Building Product (Leader) Cert. No. SGBP 3253



|                              |   |
|------------------------------|---|
| <b>Shelf Life</b>            | No expiration date if the product is stored in accordance with the storage conditions as stated in this Product Data Sheet  |
| <b>Storage Conditions</b>    | Products must be stored in their original packing, laid in a horizontal position, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements |
| <b>Dimensions</b>            | 75 x 20 x 10 mm   |
| <b>TECHNICAL INFORMATION</b> |   |
| <b>Service Temperature</b>   | - 30 °C to 80 °C  |

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

For more information, please contact the Sika Sales Personnel.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### **Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: [sales@sg.sika.com](mailto:sales@sg.sika.com)

[www.sika.com.sg](http://www.sika.com.sg)



### **Product Data Sheet**

**SikaRoof® VersiDrain® 60 Wall Joiner**

February 2026, Version 01.01

020945051450243592

SikaRoofVersiDrain60WallJoiner-en-SG-(02-2026)-1-1.pdf