Sikalastic®-870 BT Part A



Version **Revision Date:** SDS Number: Date of last issue: -

000000608389 Date of first issue: 22.08.2022 22.08.2022 1.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikalastic®-870 BT Part A

Manufacturer or supplier's details

Company Sika (Singapore) Pte Ltd.

> 28 Tuas South Ave 8 637648 Singapore

+65 6861 0632 Telephone

Emergency telephone number : +65 6861 0632

E-mail address

Telefax +65 6862 3915

2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Inhalation) Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 2

Respiratory sensitisation Category 1

Skin sensitisation Category 1

Carcinogenicity Category 2

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

Specific target organ toxicity - : Category 2

repeated exposure

(Inhalation)

GHS label elements

Hazard pictograms





Signal word Danger

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure if inhaled.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | >= 30 -< 50 |
| methylenediphenyl diisocyanate | 26447-40-5 | >= 1 -< 10 |
| 4,4`-Methylenediphenyl diisocyanate, oligomers | 25686-28-6 | >= 1 -< 10 |

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitising effects Asthmatic appearance

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Headache Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Harmful if inhaled.

Sikalastic®-870 BT Part A



Revision Date: SDS Number: Version Date of last issue: -

000000608389 22.08.2022 Date of first issue: 22.08.2022 1.0

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

Treat symptomatically. Notes to physician

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid formation of aerosol.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|-------------------------------------|--|--------|
| 4,4'-methylenediphenyl diiso- cyanate | 101-68-8 | PEL (long term) | 0.005 ppm 0.051 mg/m3 | SG OEL |
| | | TWA | 0.005 ppm | ACGIH |
| methylenediphenyl diisocya- nate | 26447-40-5 | PEL (long term) | 0.005 ppm 0.051 mg/m3 | SG OEL |
| 4,4`-Methylenediphenyl diisocyanate, oligomers | 25686-28-6 | PEL (long term) | 0.005 ppm 0.051 mg/m3 | SG OEL |
| | | TWÁ | 0.005 ppm | ACGIH |

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : pungent

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 200 °C (392 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : 1.1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Components:

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

4,4'-Methylenediphenyl diisocyanate, oligomers:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 9,400 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

: There is no data available for this product.

mation

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 2206

Proper shipping name : ISOCYANATES, TOXIC, N.O.S.

Class : 6.1
Packing group : III
Labels : 6.1

IATA-DGR

UN/ID No. : UN 2206

Proper shipping name : Isocyanates, toxic, n.o.s.

Class : 6.1
Packing group : III
Labels : Toxic
Packing instruction (cargo : 663

aircraft)

Packing instruction (passen-

ger aircraft)

655

IMDG-Code

UN number : UN 2206

Proper shipping name : ISOCYANATES, TOXIC, N.O.S.

Class : 6.1
Packing group : III
Labels : 6.1
EmS Code : F-A, S-A
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Sikalastic®-870 BT Part A



Version Revision Date: SDS Number: Date of last issue: -

1.0 22.08.2022 000000608389 Date of first issue: 22.08.2022

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Isocyanates

16. OTHER INFORMATION

Revision Date : 22.08.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SG OEL : Singapore. Workplace Safety and Health (General Provisions)

Regulations - First Schedule Permissible Exposure Limits of

Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN