

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Davco 133 PU Topcoat Part B

Product code : 100000034758

#### Manufacturer or supplier's details

Company : Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8  
637648 Singapore

Telephone : +65 6861 0632

Telefax : +65 6862 3915

E-mail address : -

Emergency telephone number : +65 6861 0632

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.

### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethylene-1,6-diisocyanate homopolymer	28182-81-2	>= 50 -< 70
2-methoxy-1-methylethyl acetate	108-65-6	>= 30 -< 50

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, phosphate	9046-01-9	>= 1 -< 2.5
cyclohexyldimethylamine	98-94-2	>= 0.25 -< 1
2-methoxypropyl acetate	70657-70-4	>= 0.1 -< 0.3

### 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects  
sensitising effects  
Cough  
Respiratory disorder  
Allergic reactions  
Excessive lachrymation  
Headache  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Harmful if inhaled.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

Dry chemical

- Unsuitable extinguishing media : Water
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use water spray to cool unopened containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- 

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.
- Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
- 

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.  
Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.
-

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products

Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : No data available

---

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	ca. 42 °C (108 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	10.8 %(V)
Lower explosion limit / Lower flammability limit	:	1.5 %(V)
Vapour pressure	:	3.1 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.05 g/cm <sup>3</sup> (25 °C (77 °F))
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	333 °C
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	> 100 mPa.s (25 °C (77 °F))
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : No hazards to be specially mentioned.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : No data available

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Harmful if inhaled.

#### Components:

##### **Hexamethylene-1,6-diisocyanate homopolymer:**

Acute oral toxicity : LD50 Oral (Rat): > 2,500 mg/kg

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

##### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

##### **cyclohexyldimethylamine:**

Acute inhalation toxicity : LC50 (Rat): 4.45 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

#### **Skin corrosion/irritation**

Not classified based on available information.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

---

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

No data available

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

#### **Product:**

Additional ecological information : There is no data available for this product.

---

## 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## 14. TRANSPORT INFORMATION

### **International Regulations**



# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

### UNRTDG

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
(Easaqua M 501, Methoxy propyl acetate)  
Class : 3  
Packing group : III  
Labels : 3

### IATA-DGR

UN/ID No. : UN 1263  
Proper shipping name : Paint related material  
(Easaqua M 501, Dowanol PMA)  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1263  
Proper shipping name : PAINT RELATED MATERIAL  
(Easaqua M 501, Dowanol PMA)  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.**

Environmental Protection and Management Act and : Not applicable  
Environmental Protection and Management (Hazardous Substances) Regulations

---

## 16. OTHER INFORMATION

# SAFETY DATA SHEET

## Davco 133 PU Topcoat Part B



Version  
1.0

Revision Date:  
11.10.2021

SDS Number:  
100000034758

Date of last issue: -  
Date of first issue: 11.10.2021

---

Date format : dd.mm.yyyy

### Full text of other abbreviations

ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service

DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic

PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.  
SG / EN