

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaCeram®-855 Part A

Manufacturer or supplier's details

Company : Sika (Shanghai) Management Co., Ltd.
NO.252, Jiangchang 3rd Road , Jing'an District, Shanghai,
China

Telephone : (86) 021 8017 1833

Emergency telephone number : +86-21-8017 1834

E-mail address : safety@davco.cn

Telefax : (86) 021 8017 1833

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : paste
Colour : white
Odour : slight

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/04/22	100000057238	Date of first issue: 2024/04/22

Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Physical and chemical hazards

Not classified based on available information.

Health hazards

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	≥ 50 -< 70
glass, oxide, chemicals	65997-17-3	≥ 30 -< 50
Quartz (SiO ₂)	14808-60-7	≥ 1 -< 10
benzyl alcohol	100-51-6	≥ 1 -< 10

4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
irritant effects
sensitising effects
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version 1.0	Revision Date: 2024/04/22	SDS Number: 100000057238	Date of last issue: - Date of first issue: 2024/04/22
----------------	------------------------------	-----------------------------	--

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Handling

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

application area.
Follow standard hygiene measures when handling chemical products

Do not breathe vapours/dust.

Avoidance of contact : No data available

Storage

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
glass, oxide, chemicals	65997-17-3	TWA (fibres)	1 fibres per cubic centimeter	ACGIH
		TWA (fibres)	1 fibres per cubic centimeter	ACGIH
Quartz (SiO ₂)	14808-60-7	PC-TWA (Total dust)	0.5 mg/m ³	CN OEL
		Further information: G1 - Carcinogenic to humans		
		PC-TWA (Respirable dust)	0.2 mg/m ³	CN OEL
		PC-TWA (Total dust)	0.7 mg/m ³	CN OEL
		PC-TWA (Total dust)	1 mg/m ³	CN OEL
		PC-TWA (Respirable dust)	0.7 mg/m ³	CN OEL
		PC-TWA (Respirable dust)	0.3 mg/m ³	CN OEL
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA	0.025 mg/m ³	ACGIH

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

		(Respirable particulate matter)		
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

Odour : slight

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

Odour Threshold	:	No data available
pH	:	No data available
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	ca. 1.32 g/cm ³ (20 °C (68 °F))
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	ca. 110,000 mPa.s (20 °C (68 °F))
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

10. STABILITY AND REACTIVITY

- Reactivity : No dangerous reaction known under conditions of normal use.
- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : No hazards to be specially mentioned.
- Conditions to avoid : No data available
- Incompatible materials : No data available
- Hazardous decomposition products : No hazardous decomposition products are known.
-

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

benzyl alcohol:

- Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

Marine pollutant : no

IATA-DGR

UN/ID No. : Not applicable

Proper shipping name : Not applicable

Class : Not applicable

Subsidiary risk : Not applicable

Packing group : Not applicable

Labels : Not applicable

Packing instruction (cargo aircraft) : Not applicable

Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable

Proper shipping name : Not applicable

Class : Not applicable

Subsidiary risk : Not applicable

Packing group : Not applicable

Labels : Not applicable

EmS Code : Not applicable

Marine pollutant : Not applicable

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version
1.0

Revision Date:
2024/04/22

SDS Number:
100000057238

Date of last issue: -
Date of first issue: 2024/04/22

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Marine pollutant : no

National Regulations

GB 6944/12268

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Marine pollutant : no

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed
Not listed

Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

16. OTHER INFORMATION

Revision Date : 2024/04/22

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average

SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



SikaCeram®-855 Part A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	2024/04/22	100000057238	Date of first issue: 2024/04/22

CN OEL / PC-TWA	:	Permissible concentration - time weighted average
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Disclaimer

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

CN / EN