Sikafloor®-2530 W LP Comp. A



Version **Revision Date:** SDS Number: Date of last issue: 28.12.2021 25.10.2022 000000601644 Date of first issue: 13.08.2020 2.1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-2530 W LP Comp. A

Manufacturer or supplier's details

Company Sika (Singapore) Pte Ltd.

> 28 Tuas South Ave 8 637648 Singapore

+65 6861 0632 Telephone

Emergency telephone number : +65 6861 0632

E-mail address

Telefax +65 6862 3915

Recommended use of the chemical and restrictions on use

Product use : Product is not intended for consumer use

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation Category 1

Specific target organ toxicity - : Category 1 (Lungs)

repeated exposure

(Inhalation)

GHS label elements

Hazard pictograms







Signal word Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

Precautionary statements : Prevention:

P260 Do not breathe mist or vapours.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Polymer from BADGE, polyethylene glycol,	362679-94-5	>= 10 -< 20
TETA and cresyl glycidyl ether		
Quartz (SiO2) <5µm	14808-60-7	>= 10 -< 20
benzyl alcohol	100-51-6	>= 1 -< 10
Fatty acids, C18-unsatd., dimers, polymer reac-	68082-29-1	>= 1 -< 2.5
tion products with tall-oil fatty acids and triethy-		
lenetetramine		
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 1 -< 3
N-methyl-2-pyrrolidone	872-50-4	>= 0.1 -< 0.3
3,6-diazaoctanethylenediamin	112-24-3	>= 0.1 -< 1

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Sikafloor®-2530 W LP Comp. A



SDS Number: Version Revision Date: Date of last issue: 28.12.2021 000000601644 Date of first issue: 13.08.2020 2.1 25.10.2022

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

> Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms and effects, both acute and

delayed

irritant effects

sensitising effects Allergic reactions

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Treat symptomatically. Notes to physician

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2) <5μm	14808-60-7	PEL (long term) (Res- pirable dust)	0.1 mg/m3	SG OEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res-	0.025 mg/m3	ACGIH

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

pirable par- ticulate mat- ter)	(Silica)	
TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
N-methyl-2-pyrrolidone	872-50-4	5-Hydroxy- N-methyl-2- pyrrolidone	Urine	End of shift (As soon as possible after ex- posure ceases)	100 mg/l	ACGIH BEI

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

Appearance : liquid

Colour : beige

Odour : amine-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

ooint

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : 1.33 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 2,000 mPa.s

Viscosity, kinematic : $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

N-methyl-2-pyrrolidone:

Acute oral toxicity : LD50 Oral (Rat): 4,150 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

3,6-diazaoctanethylenediamin:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

Sikafloor®-2530 W LP Comp. A



Version Revision Date: SDS Number: Date of last issue: 28.12.2021 000000601644 Date of first issue: 13.08.2020 2.1 25.10.2022

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

aquatic invertebrates

Exposure time: 48 h

Fatty acids, C18-unsatd., dimers, polymer reaction products with tall-oil fatty acids and tri-

ethylenetetramine:

Toxicity to fish

LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 4.34

ma/l

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.5

Sikafloor®-2530 W LP Comp. A



Version Revision Date: SDS Number: Date of last issue: 28.12.2021 000000601644 Date of first issue: 13.08.2020 2.1 25.10.2022

mq/l

Exposure time: 72 h

Toxicity to daphnia and other : aquatic invertebrates (ChronEC50 (Daphnia sp. (water flea)): 7.07 mg/l

Exposure time: 48 d

ic toxicity)

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic plants

: ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

3,6-diazaoctanethylenediamin:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

100 mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Empty remaining contents. Contaminated packaging

> Dispose of as unused product. Do not re-use empty containers.

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen-

ger aircraft)

Not applicable

IMDG-Code

UN number Not applicable Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Labels Not applicable Not applicable **EmS Code** Marine pollutant Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Not applicable

Sikafloor®-2530 W LP Comp. A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 28.12.2021

 2.1
 25.10.2022
 000000601644
 Date of first issue: 13.08.2020

16. OTHER INFORMATION

Revision Date : 25.10.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

SG OEL : Singapore. Workplace Safety and Health (General Provisions)

Regulations - First Schedule Permissible Exposure Limits of

Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN