Sikalastic®-110



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.04.2020

 2.0
 14.11.2022
 000000606572
 Date of first issue: 27.04.2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikalastic®-110

Manufacturer or supplier's details

Company : Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8 637648 Singapore

Telephone : +65 6861 0632

Emergency telephone number : +65 6861 0632

E-mail address : -

Telefax : +65 6862 3915

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2

GHS label elements

Hazard pictograms :

(!)

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ atten-

tion.

Sikalastic®-110



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.04.2020

 2.0
 14.11.2022
 000000606572
 Date of first issue: 27.04.2020

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Asphalt	8052-42-4	>= 20 -< 30
triethylamine	121-44-8	>= 1 -< 3

4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

irritant effects

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.
Causes serious eye irritation.

Notes to physician : Treat symptomatically.

Sikalastic®-110



Version Revision Date: SDS Number: Date of last issue: 27.04.2020 000000606572 14.11.2022 Date of first issue: 27.04.2020 2.0

5. FIREFIGHTING MEASURES

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions No special environmental precautions required.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Sikalastic®-110



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.04.2020

 2.0
 14.11.2022
 000000606572
 Date of first issue: 27.04.2020

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Asphalt	8052-42-4	PEL (long term) (Fumes)	5 mg/m3	SG OEL
		TWA (Fume, inhalable fraction)	0.5 mg/m3 (benzene soluble aerosol)	ACGIH
triethylamine	121-44-8	PEL (long term)	1 ppm 4.1 mg/m3	SG OEL
		PEL (short term)	5 ppm 20.7 mg/m3	SG OEL
		TWA	0.5 ppm	ACGIH
		STEL	1 ppm	ACGIH

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : black

Odour : characteristic

Sikalastic®-110



Version **Revision Date:** SDS Number: Date of last issue: 27.04.2020 14.11.2022 000000606572 Date of first issue: 27.04.2020 2.0

Odour Threshold No data available

рН 8 - 10

Melting point/range / Freezing :

Flash point

Boiling point/boiling range Not applicable

> 100 °C (212 °F)

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper

flammability limit

No data available

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure > 17 hPa (20 °C (68 °F))

Relative vapour density No data available

1.08 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

Water solubility soluble

Solubility in other solvents No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

> 7 mm2/s (40 °C (104 °F)) Viscosity, kinematic

Explosive properties No data available

Oxidizing properties No data available

10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Sikalastic®-110



Version **Revision Date:** SDS Number: Date of last issue: 27.04.2020 000000606572 Date of first issue: 27.04.2020 2.0 14.11.2022

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid No data available

No data available Incompatible materials

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

triethylamine:

Acute inhalation toxicity : LC50 (Rat): 7.22 mg/l

Exposure time: 4 h Test atmosphere: vapour

: LD50 Dermal (Rabbit): 580 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Acute dermal toxicity

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Sikalastic®-110



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.04.2020

 2.0
 14.11.2022
 000000606572
 Date of first issue: 27.04.2020

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number or ID number : Not applicable Proper shipping name : Not applicable Class : Not applicable Subsidiary risk : Not applicable Packing group : Not applicable Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

Sikalastic®-110



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.04.2020

 2.0
 14.11.2022
 000000606572
 Date of first issue: 27.04.2020

aircraft)

Packing instruction (passen- : Not applicable

ger aircraft)

IMDG-Code

UN number or ID number Not applicable Not applicable Proper shipping name Not applicable Class Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Not applicable

16. OTHER INFORMATION

Revision Date : 14.11.2022 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SG OEL : Singapore. Workplace Safety and Health (General Provisions)

Regulations - First Schedule Permissible Exposure Limits of

Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration GHS : Globally Harmonized System

IATA : International Air Transport Association

Sikalastic®-110



Version	Revision Date:	SDS Number:	Date of last issue: 27.04.2020
2.0	14.11.2022	00000606572	Date of first issue: 27.04.2020

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN