

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-264 HC Comp. B

#### Manufacturer or supplier's details

Company : **Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8  
637648 Singapore

Telephone : +65 6861 0632

Emergency telephone number : +65 6861 0632

E-mail address : -

Telefax : +65 6862 3915

#### Recommended use of the chemical and restrictions on use

Product use : Flooring system

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Category 1

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
P261 Avoid breathing mist or vapours.  
P264 Wash skin thoroughly after handling.

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
benzyl alcohol	100-51-6	>= 30 -< 50
Adduct IXA-P (epoxy amine adduct, polymer)	212580-83-1	>= 20 -< 30
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 -< 20
m-phenylenebis(methylamine)	1477-55-0	>= 10 -< 20
Hydrocarbons, C9, aromatics	64742-95-6	>= 2.5 -< 10
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 -< 5

## 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

---

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
corrosive effects  
sensitising effects  
Gastrointestinal discomfort  
Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Harmful if swallowed.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Causes severe burns.
- Notes to physician : Treat symptomatically.
- 

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	PEL (short term)	0.1 mg/m <sup>3</sup>	SG OEL

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

		C	0.018 ppm	ACGIH
--	--	---	-----------	-------

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : yellow
- Odour : amine-like
- Odour Threshold : No data available
- pH : ca. 12
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 93.3 °C (> 199.9 °F)  
(Method: closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

---

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 4.9996 hPa

Relative vapour density : No data available

Density : ca. 1.02 g/cm<sup>3</sup> (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm<sup>2</sup>/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

---

### 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**  
Harmful if swallowed.

---

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

### Components:

#### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

#### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

#### **Hydrocarbons, C9, aromatics:**

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

#### **2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### Components:

#### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Corrosive  
Method : OECD Test Guideline 404

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### Components:

#### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Causes serious eye damage.

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100  
plants mg/l  
Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l  
Exposure time: 72 h

##### m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h



# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

---

### Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic plants : (Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9 mg/l  
Exposure time: 72 h

### 2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))  
Class : 8

---

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

Packing group : II  
Labels : 8

### IATA-DGR

UN/ID No. : UN 1760  
Proper shipping name : Corrosive liquid, n.o.s.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))

Class : 8  
Packing group : II  
Labels : Corrosive  
Packing instruction (cargo aircraft) : 855  
Packing instruction (passenger aircraft) : 851

### IMDG-Code

UN number : UN 1760  
Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))

Class : 8  
Packing group : II  
Labels : 8  
EmS Code : F-A, S-B  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.**

Environmental Protection and Management Act and : Not applicable  
Environmental Protection and Management (Hazardous Substances) Regulations

---

## 16. OTHER INFORMATION

Revision Date : 25.10.2022  
Date format : dd.mm.yyyy

# SAFETY DATA SHEET

## Sikafloor®-264 HC Comp. B



Version  
3.0

Revision Date:  
25.10.2022

SDS Number:  
100000010232

Date of last issue: 13.08.2020  
Date of first issue: 03.12.2018

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
SG OEL	:	Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.
ACGIH / C	:	Ceiling limit
SG OEL / PEL (short term)	:	Permissible Exposure Level (PEL) Short Term
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SG / EN