

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikafloor®-220 W Conductive (A)

#### Manufacturer or supplier's details

Company : **Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8  
637648 Singapore

Telephone : +65 6861 0632

Emergency telephone number : +65 6861 0632

E-mail address : -

Telefax : +65 6862 3915

#### Recommended use of the chemical and restrictions on use

Product use : Epoxy coating

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Serious eye damage/eye irritation : Category 1

#### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements :

#### Prevention:

P280 Wear eye protection/ face protection.

#### Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

### Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Epoxy resin/polyamine adduct	238080-05-2	>= 3 -< 10
(2-methoxymethylethoxy)propanol	34590-94-8	>= 1 -< 10

### 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : No known significant effects or hazards.  
Excessive lachrymation  
See Section 11 for more detailed information on health effects and symptoms.  
Causes serious eye damage.
- Notes to physician : Treat symptomatically.

### 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
No special environmental precautions required.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

(2-methoxymethylethoxy)propanol	34590-94-8	PEL (long term)	100 ppm 606 mg/m <sup>3</sup>	SG OEL
		PEL (short term)	150 ppm 909 mg/m <sup>3</sup>	SG OEL

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : black
- Odour : amine-like
- Odour Threshold : No data available
- pH : ca. 9  
Concentration: 100 %
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : Not applicable

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

---

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	23 hPa
Relative vapour density	:	No data available
Density	:	ca. 1.2 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s ( 40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

---

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **(2-methoxymethylethoxy)propanol:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

##### Carcinogenicity

Not classified based on available information.

##### Reproductive toxicity

Not classified based on available information.

##### STOT - single exposure

Not classified based on available information.

##### STOT - repeated exposure

Not classified based on available information.

##### Aspiration toxicity

Not classified based on available information.

---

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

No data available

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

---

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

---

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : There is no data available for this product.

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### **UNRTDG**

UN number : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable

#### **IATA-DGR**

UN/ID No. : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
Packing instruction (cargo aircraft) : Not applicable  
Packing instruction (passenger aircraft) : Not applicable

#### **IMDG-Code**

UN number : Not applicable  
Proper shipping name : Not applicable  
Class : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
EmS Code : Not applicable

---

# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version 1.1      Revision Date: 12.08.2022      SDS Number: 000000043567      Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

---

Marine pollutant : Not applicable

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Special precautions for user**

Not applicable

---

### 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.**

Environmental Protection and Management Act and : Not applicable  
Environmental Protection and Management (Hazardous Substances) Regulations

---

### 16. OTHER INFORMATION

Revision Date : 12.08.2022  
Date format : dd.mm.yyyy

**Full text of other abbreviations**

SG OEL : Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term  
SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road

CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)

LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)

MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg-

---



# SAFETY DATA SHEET

## Sikafloor®-220 W Conductive (A)



Version  
1.1

Revision Date:  
12.08.2022

SDS Number:  
000000043567

Date of last issue: 13.08.2020  
Date of first issue: 13.08.2020

---

SVHC : Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency  
vPvB : Substances of Very High Concern  
: Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SG / EN