



Davco

101

SKIM COAT PASTE, WALL AND CEILING



ECO FRIENDLY



LOW CARBON FOOTPRINT



EASE OF USE

DESCRIPTION

Davco 101 is a white-grey-coloured paste made of synthetic resins, fibres, additives and inorganic fillers.

Davco 101 is designed to eliminate the surface defects such as bubbles, honeycombs.

Davco 101 corrects unevenness of the substrate and can be applied in several layers.

ADVANTAGES

- Finished surface colour up to the binder.
- Easy to use.
- Adjustable consistency.
- Very good adhesion to substrate.
- Easy for painting and wall-covering.
- Indoors and outdoors use.
- Keep a nice surface.

Acceptable substrates

- Exterior (excepted plaster mixture) / Interior:
- Form-molded concrete
- Reinforced concrete walls
- Concrete slabs
- Modular panels
- Blown clay aggregate concrete
- Conventional coatings.

Interior only, in plaster mixture:

- Cellular concrete
- Plaster and gypsum wallboard

Related coverings

- Plastic facing coating
- Paints
- Wallpaper
- Skim Coat
- Wall Textile

TECHNICAL DATA

Appearance	: White-grey paste
Paste density	: 1.3 ± 0.1
pH	: 11
Particle size	: 0.04 to 0.12mm
Consumption	: 0.4 - 0.6 kg/m ² /mm
Pot life	: 30 min
Lapse of time between 2 layers	: 2 to 4 hours
Time before covering	: 7 days

Physical Data


Bond strength by shear	
ASTM C882	7 days : > 5 MPa
	28 days : > 7 MPa

Compressive strength	
ASTM C109	7 days : 18 MPa
	28 days : 22 MPa

(All specimens are prepared by mixing one part of cement with one part of Davco 101)

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

PAREX
Building expertise, together





101

INSTRUCTIONS

Substrate Preparation

- The substrate must be clean, sound and free from dust, oil, grease or surface contaminants.
- Remove any cement laitance, formwork traces and loosely bonded particles.
- Moisturise the substrate before application.

Mixing

- Mix Davco 101 (weight by weight) with 0.5 to 1 part of cement or plaster until a lump-free homogeneous paste is reached.
- Do not add water.

Application

Apply with a trowel or a putty knife.

PACKAGING

25 kg/bucket.

STORAGE

Freeze-free and shadow area.

SHELF LIFE

1 year in unopened packaging.

HEALTH & SAFETY

Refer to safety data sheet.

Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website www.parexgroup.com.sg

PAREXGROUP PTE LTD

28 TUAS SOUTH AVENUE 8, SINGAPORE 637648

TEL: (65) 6861 0632 FAX: (65) 6862 3915

EMAIL: SALES@PAREXGROUP.COM.SG

WEBSITE: WWW.PAREXGROUP.COM.SG



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ParexGroup, a French multi-national company with headquarters in Paris, is a leading manufacturer of speciality products for the construction industry with operations in more than 20 countries, and our 2700 people around the world are the cornerstone of our growing organization.

Updated Jun 2017

