



# TUFSEAL ECO

## CLEAR PU SEALER



**COLOURLESS  
SEALER**



**WATER BASED**



**REPELS  
WATER**

### DESCRIPTION

Davco Tufseal ECO is an environmentally friendly and highly durable non-yellowing clear polyurethane sealer. Davco Tufseal ECO, a water based sealer with low VOC, non toxic and safe to use.

### USES

- As a protective sealer for a wide range of surfaces such as unglazed quarry tiles, slates, pavers and roof tiles.
- As a sealer to dustproof concrete, precast concrete, masonry.
- As a water repellent sealer to protect and enhance the durability of brick walls.
- Seals porous surface to prevent fungus and algae growth.

### ADVANTAGES

- Prevent migration of water stains, dirt, oil and grease.
- Non-yellowing when exposed to sunlight.
- Excellent water repelling characteristic.
- Protect substrate against deterioration, weathering and carbonation.
- Unaffected by most alkali, mild acid, oil, grease, detergent and some mild solvent.

### SURFACE PREPARATION

- Ensure that the surface is clean, dry and free from stains, dirt, grease, fungus/algae and any loose matter.
- New concrete surface should have a minimum of 7 days curing period before applying Davco Tufseal ECO.

### APPLICATION

- Apply Davco Tufseal ECO in corner of sample substrate to check for compatibility and change in tonality.
- No mixing is required, just stir the material before use to prevent settlement due to storage and transportation.
- Apply Davco Tufseal ECO directly from the can.
- Apply a minimum of 2 coats using brush, roller or spray.
- For new concrete surfaces, seal and harden freshly laid concrete using Davco Tufseal ECO.
- Ensure the surface is dry before applying Davco Tufseal ECO.
- Allow the sealer to dry before trafficking. Tack free-approx. 30 minutes. Trafficable-approx. 2 hours.
- Davco Tufseal ECO will seal in dirt and stains if not removed prior to application.

BUILDING TRUST





# TUFSEAL ECO

## COVERAGE

Depending on the porosity of the surface to be applied, 6 - 8m<sup>2</sup> per litre. (as a guide for concrete surface)

## PACKAGING

Available in 20 litres container.

## SHELF LIFE

Shelf life of 12 months when stored in a cool dry place in unopened containers.

## CLEANING

Clean up Davco Tufseal ECO with water.

## HEALTH AND SAFETY

Protective gloves and goggles should be used when handling this product. In cases of eyes splashes or excessive skin contact, thoroughly flush with water. If any ill effects should occur, seek medical attention. Refer to safety data sheet.

## Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website [www.sika.com.sg](http://www.sika.com.sg)

## Sika (Singapore) Pte Ltd.

28 Tuas South Avenue 8 Singapore 637648

Tel: (65) 6861 0632 • Fax: (65) 6862 1172

Email: [sales@sg.sika.com](mailto:sales@sg.sika.com)

Website: [www.sika.com.sg](http://www.sika.com.sg)

Online Store: [davco-online.com.sg](http://davco-online.com.sg)



Certificate SG09/02195



Certificate SG95/06111



Certificate SG09/50075



ISO 14064 : 2006  
Certificate GMS-C / GHG / 0002



Updated TM62 Jul 2018

