



# PRIMER XP

## ACRYLIC PRIMER

### DESCRIPTION

Davco Primer XP is a solvent based acrylic primer for concrete, masonry, dry wall or metal surface prior to laying Davco waterproofing membrane and cementitious coatings as part of the overall system.

### USES

To improve adhesion of the Davco waterproofing membrane and cement base overlaying products.

To seal and prepare concrete or masonry surfaces for waterproofing and receiving of cementitious finishing and coating products.

### APPLICATION

Apply directly from the pail. Ensure a clear sheen after application and allow to dry before applying Davco waterproofing membrane or cementitious coatings. Drying time is approximately 15 - 30 minutes depending on temperature and substrate condition.

For concrete and masonry substrates to be primed using Davco Primer XP, the surfaces must be bare without any coating.

### HEALTH AND SAFETY

This product contains solvent and is flammable. Do not use near naked flame or smoke during handling. Wear protective gloves and safety goggles. Avoid excessive inhalation. In case of skin contact or accidental eye contamination, wash with plenty of clean water. Refer to safety data sheet.

### TECHNICAL DATA

Colour	Clear
Specific Gravity	0.92
Drying Time	15 - 30 mins

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

### COVERAGE

Approximately 9 - 12m<sup>2</sup> per litre depending on the substrate condition.

### PACKAGING

Davco Primer XP is available in 20 litres containers.

### SHELF LIFE

Up to 12 months in an unopened container, when stored in a cool dry place.

#### Disclaimer

The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subjected to changes without prior notice. Before application, customers and users are requested to check that they have the latest version of this document from our website [www.sika.com.sg](http://www.sika.com.sg)

Sika (Singapore) Pte Ltd.  
28 Tuas South Avenue 8 Singapore 637648  
Tel: (65) 6861 0632 • Fax: (65) 6862 1172  
Email: [sales@sg.sika.com](mailto:sales@sg.sika.com)  
Website: [www.sika.com.sg](http://www.sika.com.sg)  
Online Store: [davco-online.com.sg](http://davco-online.com.sg)

BUILDING TRUST

