

## PRODUCT DATA SHEET

# Sika® Plastiment® R 300

(formerly MasterPozzolith® R 300)

## RETARDING TYPE CONCRETE IMPROVING ADMIXTURE

## DESCRIPTION

Sika® Plastiment® R 300 is a ready-to-use liquid admixture for making better, more uniform and more predictable high quality concrete. It retards the setting time to facilitate placing and finishing.

Sika® Plastiment® R 300 has been formulated to meet the requirements of ASTM C494 for Types B and D admixtures. Sika® Plastiment® R 300 is compatible with all cements meeting recognised international standards.

## USES

- All types of concrete where retardation of set and improved performance are required.
- Improving pumped concrete and conventionally placed concrete.
- Improving plain, reinforced, precast, prestressed, light weight or standard weight concrete.

## CHARACTERISTICS / ADVANTAGES

- Good water reduction - Improves watertightness. Greater durability. Increases compressive, flexural and bond strengths
- Good workability - Easier placement
- Good cohesion - Reduces segregation

## PRODUCT INFORMATION

<b>Packaging</b>	205 L drum
<b>Shelf Life</b>	Stored for 12 months in tightly sealed original drums
<b>Storage Conditions</b>	Stored at temperatures above 5°C. If found to be frozen, thaw it and reconstitute by stirring.

## APPLICATION INFORMATION

<b>Recommended Dosage</b>	Sika® Plastiment® R 300 is recommended for use at a dosage rate of 200 - 350 ml per 100 kg of cementitious materials. Variations in the job conditions and concrete making materials employed may require dosage rates outside the recommended range. Consult your Sika representative for assistance in determining the dosage rate.
<b>Dispensing</b>	Sika® Plastiment® R 300 can be added into the mixing water, or can be added to the wet concrete after the mixing water has been added. The addition of Sika® Plastiment® R 300 to a dry concrete mix is not recommended. A separate dispenser and feed line must be used.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika (Singapore) Pte Ltd.

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: sales@sg.sika.com

www.sika.com.sg



### Product Data Sheet

Sika® Plastiment® R 300

March 2024, Version 01.01

02130300000002189

SikaPlastimentR300-en-SG-(03-2024)-1-1.pdf