

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : SikaFloor® Marine KG-404 N

Manufacturer or supplier's details

Company : **Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8
637648 Singapore

Telephone : +65 6861 0632

Emergency telephone number : +65 6861 0632

E-mail address : -

Telefax : +65 6862 3915

Recommended use of the chemical and restrictions on use

Product use : Mortar

2. HAZARDS IDENTIFICATION

GHS Classification

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Quartz (SiO ₂) | 14808-60-7 | >= 30 -< 50 |
| Cement (chromium reduced) | 65997-15-1 | >= 20 -< 30 |
| Cement, portland, chemicals | 65997-15-1 | >= 10 -< 20 |

4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.
Consult a physician after significant exposure.

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



| | | | |
|----------------|------------------------------|-----------------------------|---|
| Version 2.0 | Revision Date: 12.12.2022 | SDS Number: 000000605132 | Date of last issue: 13.04.2019 Date of first issue: 13.04.2019 |
|----------------|------------------------------|-----------------------------|---|

- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitising effects
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
- Notes to physician : Treat symptomatically.
-

5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Use personal protective equipment.
Avoid breathing dust.
-

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

- agency procedures : Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
- Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.
- Advice on safe handling : Do not breathe vapours/dust.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.
- Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------------|------------|-------------------------------------|--|--------|
| Quartz (SiO ₂) | 14808-60-7 | PEL (long term) (Respirable dust) | 0.1 mg/m ³ | SG OEL |
| | | TWA (Respirable particulate matter) | 0.025 mg/m ³ | ACGIH |
| | | TWA (Respirable particulate matter) | 0.025 mg/m ³ (Silica) | ACGIH |

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

| | | | | |
|-----------------------------|------------|-------------------------------------|----------------------------------|--------|
| | | ter) | | |
| | | TWA (Respirable particulate matter) | 0.025 mg/m ³ | ACGIH |
| | | TWA (Respirable particulate matter) | 0.025 mg/m ³ (Silica) | ACGIH |
| Cement (chromium reduced) | 65997-15-1 | PEL (long term) | 10 mg/m ³ | SG OEL |
| | | TWA (Respirable particulate matter) | 1 mg/m ³ | ACGIH |
| Cement, portland, chemicals | 65997-15-1 | PEL (long term) | 10 mg/m ³ | SG OEL |
| | | TWA (Respirable particulate matter) | 1 mg/m ³ | ACGIH |

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

Appearance : powder

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : > 10 (20 °C (68 °F))
Concentration: 50 %

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : Not applicable

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1 g/cm³ (20 °C (68 °F))

Solubility(ies)

 Water solubility : insoluble

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : Not applicable

Explosive properties : No data available

Oxidizing properties : No data available

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

10. STABILITY AND REACTIVITY

- Reactivity : No dangerous reaction known under conditions of normal use.
- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : No hazards to be specially mentioned.
- Conditions to avoid : No data available
- Incompatible materials : No data available
-

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number or ID number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo) : Not applicable

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

aircraft)
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number or ID number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable
Environmental Protection and Management (Hazardous Substances) Regulations

16. OTHER INFORMATION

Revision Date : 12.12.2022
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
SG OEL : Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.
ACGIH / TWA : 8-hour, time-weighted average
SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at

SAFETY DATA SHEET

SikaFloor® Marine KG-404 N



Version
2.0

Revision Date:
12.12.2022

SDS Number:
000000605132

Date of last issue: 13.04.2019
Date of first issue: 13.04.2019

| | | |
|--------|---|--|
| LC50 | : | once, which causes the death of 50% (one half) of a group of test animals) : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | : Occupational Exposure Limit |
| PBT | : | : Persistent, bioaccumulative and toxic |
| PNEC | : | : Predicted no effect concentration |
| REACH | : | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : | : Substances of Very High Concern |
| vPvB | : | : Very persistent and very bioaccumulative |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.
SG / EN