# Sikalastic® HLM 5000 R



Date of last issue: -Version **Revision Date:** SDS Number:

18.04.2024 100000056962 Date of first issue: 18.04.2024 1.0

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product identifier** Sikalastic® HLM 5000 R

Recommended use of the chemical and restrictions on use Product use : Liquid applied membranes

Manufacturer or supplier's details

Sika (Singapore) Pte Ltd. Company

> 28 Tuas South Ave 8 637648 Singapore

Telephone +65 6861 0632

Emergency telephone num- : +65 6861 0632

ber

E-mail address

Telefax +65 6862 3915

# 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Serious eye damage/eye irri-

tation

Category 2

Specific target organ toxicity - :

repeated exposure

Category 1

**GHS** label elements

Hazard pictograms





Signal word Danger

Hazard statements H319 Causes serious eye irritation.

H372 Causes damage to organs through prolonged or repeated

exposure.

Precautionary statements Prevention:

> P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear eye protection/ face protection.

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

18.04.2024 100000056962 Date of first issue: 18.04.2024 1.0

## Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ at-

tention.

#### Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

## Other hazards which do not result in classification

None known.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Chlorinated paraffin	106232-86-4	>= 10 -< 20
mesitylene	108-67-8	>= 2.5 -< 10
tin bis(2-ethylhexanoate)	301-10-0	>= 0.1 -< 1

#### 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Causes serious eye irritation.

Causes damage to organs through prolonged or repeated

exposure.

# Sikalastic® HLM 5000 R



**Revision Date:** Version SDS Number: Date of last issue: -

18.04.2024 100000056962 Date of first issue: 18.04.2024 1.0

irritant effects

Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Hazardous combustion prod-

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
mesitylene	108-67-8	PEL (long term)	25 ppm 123 mg/m3	SG OEL
		TWA	10 ppm	ACGIH

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

Colour : white

Odour : No data available

Odour Threshold : No data available

pH : 6-7

Melting point/range / Freezing :

ooint

No data available

Boiling point/boiling range : No data available

Flash point : ca. 66 °C (151 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.1 hPa

Relative vapour density : No data available

Density : 1.30 - 1.40 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : 15,000 - 25,000 mPa.s (20 °C (68 °F))

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

#### 10. STABILITY AND REACTIVITY

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No hazardous decomposition products are known.

#### 11. TOXICOLOGICAL INFORMATION

## **Acute toxicity**

Not classified due to lack of data.

## **Components:**

tin bis(2-ethylhexanoate):

Acute oral toxicity : LD50 Oral: 3,400 mg/kg

### Skin corrosion/irritation

Not classified due to lack of data.

## Serious eye damage/eye irritation

Causes serious eye irritation.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified due to lack of data.

## Respiratory sensitisation

Not classified due to lack of data.

## Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

Not classified due to lack of data.

## Reproductive toxicity

Not classified due to lack of data.

#### STOT - single exposure

Not classified due to lack of data.

#### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

## **Aspiration toxicity**

Not classified due to lack of data.

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

#### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

### **Components:**

tin bis(2-ethylhexanoate):

Toxicity to algae/aquatic plants

EC50 (algae): 6.9 mg/l Exposure time: 72 h

#### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

# Mobility in soil

No data available

#### Other adverse effects

## **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

### 13. DISPOSAL CONSIDERATIONS

#### **Disposal methods**

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### 14. TRANSPORT INFORMATION

#### **International Regulations**

#### **UNRTDG**

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

**IATA-DGR** 

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : Not applicable

ger aircraft)

**IMDG-Code** 

**UN** number Not applicable Proper shipping name Not applicable Class Not applicable Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable EmS Code Not applicable Marine pollutant

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations specific for the product in question

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Not applicable

## 16. OTHER INFORMATION

Revision Date : 18.04.2024 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SG OEL : Singapore. Workplace Safety and Health (General Provisions)

Regulations - First Schedule Permissible Exposure Limits of

# Sikalastic® HLM 5000 R



Version Revision Date: SDS Number: Date of last issue: -

1.0 18.04.2024 100000056962 Date of first issue: 18.04.2024

Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNFL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing. SG / EN