

## PRODUCT DATA SHEET

# Sarnafil® PVC Walkway Pad (CN)

### INJECTION MOULDED PVC WALKWAY PAD

#### DESCRIPTION

Sarnafil® PVC Walkway Pad is made of high quality PVC by injection moulding procedure.

#### USES

Sarnafil® PVC Walkway Pad is used to provide a durable slip resisting walkway for roof maintenance or access on any Sarnafil® PVC or Sikaplan® PVC roofing system.

#### CHARACTERISTICS / ADVANTAGES

- Resistant to permanent UV irradiation
- Outstanding slip resistant surface
- Hot air welding without use of open flames
- Rainwater drainage from beneath the Sarnafil® PVC Walkway Pad is provided by a network of moulded channels

#### APPROVALS / STANDARDS

Quality management system EN ISO 9001/14001

#### PRODUCT INFORMATION

<b>Chemical Base</b>	Polyvinyl Chloride (PVC)
<b>Packaging</b>	20 pcs / box
<b>Appearance / Colour</b>	Grey
<b>Shelf Life</b>	Sarnafil® PVC Walkway Pad does not expire when properly stored.
<b>Storage Conditions</b>	Sarnafil® PVC Walkway Pad shall be stored in dry conditions.
<b>Surface</b>	Chevron pattern with an alternating rib height of the embossing
<b>Length</b>	605 ± 8 mm
<b>Width</b>	600 ± 10 mm (exclude welding lap)
<b>Thickness</b>	7 mm (± 0.2 mm) including 3 mm non-slip chevron pattern embossing
<b>System Structure</b>	Compatible products: Sarnafil® PVC -types Sikaplan® PVC -types

## APPLICATION INFORMATION

**Ambient Air Temperature** -20 °C min. / +60 °C max.

**Substrate Temperature** -30 °C min. / +60 °C max.

### APPLICATION

Installation works must be carried out only by Sika® trained and approved contractors, experienced in this type of application..

Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.

Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

### APPLICATION METHOD / TOOLS

According to the latest installation instructions for Sarnafil®.

Sarnafil® PVC Walkway Pad is installed on site by hot air welding the welding tabs directly onto the Sarnafil® G/S or Sikaplan® PVC membrane.

- Mark a line (e.g. chalk line) in the direction of the installation
- Lay the walkway pads along the marked line
- If arranged in a row, move the pads against the two spacers
- Overlap the welding tabs in the running direction of the welding machine

### FURTHER DOCUMENTS

Geographical / Climate

The use of Sarnafil® PVC Walkway Pad is limited to geographical locations with average monthly minimum temperatures of -50 °C.

Permanent ambient temperature during use is limited to +50 °C.

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

**Sika (Singapore) Pte Ltd.**

28 Tuas South Ave 8

Singapore 637648

Phone: +65 6861 0632

Fax: +65 6862 3915

Email: sales@sg.sika.com

www.sika.com.sg



**Product Data Sheet**

**Sarnafil® PVC Walkway Pad (CN)**

August 2020, Version 01.01

020945012150002003

## ECOLOGY, HEALTH AND SAFETY

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SarnafilPVCWalkwayPadCN-en-SG-(08-2020)-1-1.pdf