

PRODUCT DATA SHEET

SikaProof® ExTape-150

SELF-ADHESIVE TAPE FOR EXTERNAL JOINTING OF SIKAPROOF A WATERPROOFING SYSTEM

DESCRIPTION

SikaProof® ExTape-150 is a self-adhesive tape based on a butyl adhesive for external jointing and detailing on SikaProof® A & P membrane systems. The tape is composed of a yellow carrier film and a divided release liner.

USES

SikaProof® ExTape-150 may only be used by experienced professionals.

- Sealing transverse overlap joints, connections and details within the SikaProof® A & P membrane systems.

CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing ability
- Simple and fast to install
- Divided release liner for easy installation

PRODUCT INFORMATION

Packaging	4 rolls packed in one box. Individual roll size: Length 20 m/ Width 150 mm
Appearance / Colour	Top layer yellow carrier film coated with black butyl adhesive and bottom layer white divided release liner.
Shelf Life	24 months from date of production
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between + 5 °C and + 30 °C. Always refer to packaging.
Thickness	1.10 mm

SYSTEM INFORMATION

System Structure

System Components

- SikaProof® A-05 or A-08 /HC or A-12 /HC sheet membranes
- SikaProof P-12 self-adhesive sheet membrane
- SikaProof® Tape-150 A self-adhesive tape for internal jointing
- SikaProof® ExTape-150 self-adhesive tape for external jointing

APPLICATION INFORMATION

Ambient Air Temperature	+5 °C min. / +35 °C max.
Substrate Temperature	Substrate bonding surface: Minimum +5 °C (Refer to important considerations for more information)

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the light yellow SikaProof® membrane side. It must be dry, clean and free of any materials that could impair adhesion.

If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

Remove the release liner, apply onto the outside / membrane side of the membrane and press tape firmly using a pressure roller.

For the SikaProof® A system, SikaProof® ExTape-150 is used together with SikaProof® Tape-150 A for easy, fast and secure double bonding of joints and connections.

FURTHER DOCUMENTS

- Sika® Method Statement: SikaProof® A/H/C
- Sika® Method Statement: SikaProof® P

LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- The substrate quality and conditions must be fulfilled.
- If SikaProof® ExTape-150 has to be applied under wet conditions or temperatures below +5 °C. Exceptions are possible under special circumstances with appropriate precautions. Contact Sika® Technical Services for more information.
- The SikaProof® ExTape-150 is not permanently UV and weather resistant. Therefore the membrane system must not be installed on structures permanently exposed to UV light and weathering.
- SikaProof® ExTape-150 has to be protected as soon as possible or at the latest after 90 days or before the backfilling, whichever occurs first.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Singapore) Pte Ltd
66A Sungei Kadut Street 1
Singapore 729368
Phone: +65 6368 0883
Fax: +65 6368 6636
Email: sikasing@sg.sika.com
www.sika.com.sg



Product Data Sheet
SikaProof® ExTape-150
January 2019, Version 01.01
020704210220000002

SikaProofExTape-150-en-SG-(01-2019)-1-1.pdf

